

KX12型 多接点转换开关
ROTARY SWITCH

K16型 脉冲开关
PULSE SWITCH



主要性能	Main performance	KX12型	K16型
额定功率	Rated power	DC 24V 25mA	DC 16V 0.1A
开关接触电阻	Switch contact resistance	≤ 100mΩ	≤ 50mΩ
旋转力矩	Rotation torque	20mN.m-80mN.m	8mN.m-25mN.m
耐电压	Withstand Voltage	100V Min	
绝缘电阻	Contact resistance	≥ 100MΩ (DC 100V)	
开关寿命	Switch life	20000次 (开、关)	10000次 (开、关)

KX12内部路线表: (● 为ON状态, ○ 为OFF状态)

端子	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
1	●	○	●	○	●	○	●	○	●	○	●	○	●	○	●	○
2	●	●	○	○	●	●	○	○	●	●	○	○	●	●	○	○
3	●	●	●	●	○	○	○	○	●	●	●	●	○	○	○	○
4	●	●	●	●	●	●	●	●	○	○	○	○	○	○	○	○
C	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

订货合同填写示例 Model for filling out order contact

KX12 A C1 P4 D16
 | | | | |
 开关 安装 公共 输出 软定
 型号 形式 端数 端数 位数