

WH09A型
WH0912型

绝缘轴旋转式合成碳膜电位器
INSULATED SHAFT, ROTARY CARBON COMPOSITION POTENTIOMETERS



主要性能	Main performance	WH09A型	WH0912型
额定功率	Rated power	0.05W	0.03W
最高使用电压	Max. operating Voltage	DC 50V	
阻值范围及偏差	Resistance range & tolerance	500Ω -- 1MΩ	± 20%
电阻规律	Resistance taper	A、B、C	A、B、C、MN
终端电阻	End resistance	R < 50KΩ 20Ω Max	R ≥ 50KΩ 50Ω Max
转动噪声	Rotational noise	≤ 47mV	
同步误差	Tracking error	——	± 3dB以内 (-40--0dB)
旋转力矩	Rotation torque	1--8mN. m	
总机械行程	Total mechanical travel	280° ± 10°	
机械耐久性	Mechanical endurance	10000周 Cycles	

订货合同填写示例 Model for filling out order contact

WH09 A - 1 A S □ - 10KΩ A - F25

型号 A: 单联 1: 立式 安装 支架 D带定位 标称阻值 电阻 轴型式
 12: 双联 2: 卧式 高度 形式 J带棘轮 规律 及长度

绝缘轴轴端形式及名称		WH09A长度尺寸	WH0912长度尺寸																						
F轴		<table border="1"> <tr> <td>L</td> <td>15</td> <td>20</td> <td>25</td> <td>30</td> <td>35</td> </tr> <tr> <td>l</td> <td>6</td> <td>7</td> <td>12</td> <td>12</td> <td>12</td> </tr> </table>	L	15	20	25	30	35	l	6	7	12	12	12	<table border="1"> <tr> <td>L</td> <td>15</td> <td>20</td> <td>25</td> </tr> <tr> <td>l</td> <td>6</td> <td>7</td> <td>12</td> </tr> </table>	L	15	20	25	l	6	7	12		
L	15	20	25	30	35																				
l	6	7	12	12	12																				
L	15	20	25																						
l	6	7	12																						
U轴		<table border="1"> <tr> <td>L</td> <td>15</td> <td>20</td> <td>25</td> <td>30</td> <td>35</td> </tr> <tr> <td>l</td> <td>6</td> <td>7</td> <td>7</td> <td>7</td> <td>7</td> </tr> </table>	L	15	20	25	30	35	l	6	7	7	7	7	<table border="1"> <tr> <td>L</td> <td>15</td> <td>20</td> <td>25</td> </tr> <tr> <td>l</td> <td>6</td> <td>7</td> <td>12</td> </tr> </table>	L	15	20	25	l	6	7	12		
L	15	20	25	30	35																				
l	6	7	7	7	7																				
L	15	20	25																						
l	6	7	12																						
K轴		<table border="1"> <tr> <td>L</td> <td>15</td> <td>20</td> <td>25</td> <td>30</td> <td>35</td> <td>40</td> </tr> <tr> <td>l</td> <td>6</td> <td>7</td> <td>7</td> <td>7</td> <td>7</td> <td>7</td> </tr> </table>	L	15	20	25	30	35	40	l	6	7	7	7	7	7	<table border="1"> <tr> <td>L</td> <td>15</td> <td>20</td> <td>25</td> </tr> <tr> <td>l</td> <td>6</td> <td>7</td> <td>12</td> </tr> </table>	L	15	20	25	l	6	7	12
L	15	20	25	30	35	40																			
l	6	7	7	7	7	7																			
L	15	20	25																						
l	6	7	12																						
T轴		<table border="1"> <tr> <td>L</td> <td>9.5</td> <td>15</td> <td>20</td> </tr> <tr> <td>l</td> <td>——</td> <td>6</td> <td>7</td> </tr> </table>	L	9.5	15	20	l	——	6	7	——														
L	9.5	15	20																						
l	——	6	7																						